

# Technical data sheet

## Product features



### Slicing machine, 220 mm Teflon blade

|              |                                  |                  |
|--------------|----------------------------------|------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00014108         |
| GSE 220 T    | <b>A group of articles - web</b> | Cutting machines |

- Blade type: Teflon
- Blade diameter [mm]: 220
- Cutting thickness [mm]: 0 - 14
- Useful Cut [mm]: 170 x 155
- Transfer type: Strappy
- Material: Aluminium
- Safety cover: transparent plexiglass
- Safety element: transparent finger protection  
stainless steel knife guard ring  
stainless steel blade guard
- Table position: Oblique
- On/Off button: Yes
- Continuous work limit: 10 min running, 5 min rest

|                            |          |                               |                    |
|----------------------------|----------|-------------------------------|--------------------|
| <b>SAP Code</b>            | 00014108 | <b>Loading</b>                | 230 V / 1N - 50 Hz |
| <b>Net Width [mm]</b>      | 440      | <b>Blade type</b>             | Teflon             |
| <b>Net Depth [mm]</b>      | 380      | <b>Blade diameter [mm]</b>    | 220                |
| <b>Net Height [mm]</b>     | 320      | <b>Cutting thickness [mm]</b> | 0 - 14             |
| <b>Net Weight [kg]</b>     | 10.00    | <b>Useful Cut [mm]</b>        | 170 x 155          |
| <b>Power electric [kW]</b> | 0.160    |                               |                    |

# Technical data sheet

Technical drawing



**Slicing machine, 220 mm Teflon blade**

|              |                                  |                  |
|--------------|----------------------------------|------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00014108         |
| GSE 220 T    | <b>A group of articles - web</b> | Cutting machines |

# Technical data sheet

## Technical parameters



### Slicing machine, 220 mm Teflon blade

|              |                                  |                  |
|--------------|----------------------------------|------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00014108         |
| GSE 220 T    | <b>A group of articles - web</b> | Cutting machines |

**1. SAP Code:**

00014108

**2. Net Width [mm]:**

440

**3. Net Depth [mm]:**

380

**4. Net Height [mm]:**

320

**5. Net Weight [kg]:**

10.00

**6. Gross Width [mm]:**

500

**7. Gross depth [mm]:**

400

**8. Gross Height [mm]:**

580

**9. Gross Weight [kg]:**

12.00

**10. Device type:**

Electric unit

**11. Material:**

Aluminium

**12. Power electric [kW]:**

0.160

**13. Loading:**

230 V / 1N - 50 Hz

**14. Control type:**

Mechanical

**15. Safety cover:**

transparent plexiglass

**16. Safety element:**

transparent finger protection  
stainless steel knife guard ring  
stainless steel blade guard

**17. Engine protection:**

fan and overheating protection

**18. Adjustable feet:**

Yes

**19. Main switch:**

Yes

**20. Transfer type:**

Strappy

**21. Standard equipment for device:**

grinding wheel fixed to the device

**22. Additional information:**

knife is mounted obliquely, via double ball bearing  
the blade is made of non-stick steel with adhesive grooves  
massive food holder  
non-stick blade

**23. Blade type:**

Teflon

**24. Blade diameter [mm]:**

220

# Technical data sheet

## Technical parameters



### Slicing machine, 220 mm Teflon blade

|              |                                  |                  |
|--------------|----------------------------------|------------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00014108         |
| GSE 220 T    | <b>A group of articles - web</b> | Cutting machines |

**25. Useful Cut [mm]:**

170 x 155

**26. On/Off button:**

Yes

**27. Continous work limit:**

10 min running, 5 min rest

**28. Removable moving table:**

Yes

**29. Anti-adhesive blade treatment:**

Yes

**30. Table position:**

Oblique

**31. Blade cover material:**

Stainless steel

**32. Sharpening device:**

Integrated

**33. Cutting thickness [mm]:**

0 - 14

**34. Cross-section of conductors CU [mm<sup>2</sup>]:**

0,5