

Technical data sheet

Product features



Knife sterilizer UV sterilization 66x20

Model	SAP Code	00004227
SUV 66	A group of articles - web	Knife sterilizers



- Material: Stainless steel
- Minimum device temperature [°C]: 30
- Maximum device temperature [°C]: 90
- Protection of controls: IPX4
- Timer: Yes
- Safety Microswitch: Yes

SAP Code	00004227	Net Weight [kg]	8.50
Net Width [mm]	660	Power electric [kW]	0.030
Net Depth [mm]	200	Loading	230 V / 1N - 50 Hz
Net Height [mm]	660		

Technical data sheet

Technical drawing



Knife sterilizer UV sterilization 66x20

Model	SAP Code	00004227
SUV 66	A group of articles - web	Knife sterilizers

Technical data sheet



Product benefits

Knife sterilizer UV sterilization 66x20

Model	SAP Code	00004227
SUV 66	A group of articles - web	Knife sterilizers

1

All-stainless design

only stainless steel intended for food contact is used

- absolutely rust-proof and non-magnetic design
- resists even weak acids easier compliance with hygiene standards (HACCP); easy maintenance and cleaning

2

Run and warm-up light

optical possibility to check the status of the device

- the operator immediately knows the on/off, heating/ non-heating state of the appliance

3

Sterilization using UV radiation

vyčištění nože nedochází k tupení ostří

- hygienic and clean knife
- no other chemicals used

4

Magnetic bar for attaching the legs

convenient attachment of knives in the sterilizer

- the blades do not crash into each other convenient for the operator
- safer handling

Technical data sheet

Technical parameters



Knife sterilizer UV sterilization 66x20

Model	SAP Code	00004227
SUV 66	A group of articles - web	Knife sterilizers

1. SAP Code:

00004227

2. Net Width [mm]:

660

3. Net Depth [mm]:

200

4. Net Height [mm]:

660

5. Net Weight [kg]:

8.50

6. Gross Width [mm]:

670

7. Gross depth [mm]:

210

8. Gross Height [mm]:

670

9. Gross Weight [kg]:

9.50

10. Device type:

Electric unit

11. Material:

Stainless steel

12. Power electric [kW]:

0.030

13. Loading:

230 V / 1N - 50 Hz

14. Minimum device temperature [°C]:

30

15. Maximum device temperature [°C]:

90

16. Protection of controls:

IPX4

17. Timer:

Yes

18. Safety Microswitch:

Yes