

# Technical data sheet

## Product features



### Conveyor toaster 2x holders with regulation

|              |                                  |          |
|--------------|----------------------------------|----------|
| <b>Model</b> | <b>SAP Code</b>                  | 00004519 |
| TN 30 plus   | <b>A group of articles - web</b> | Toasters |



- Material: Stainless steel
- Indicators: operation and warm-up
- Removable rear wall of the device: Yes
- Width of internal part [mm]: 305
- Depth of internal part [mm]: 500
- Heating location: Upper and lower

|                        |          |                            |                    |
|------------------------|----------|----------------------------|--------------------|
| <b>SAP Code</b>        | 00004519 | <b>Net Weight [kg]</b>     | 22.00              |
| <b>Net Width [mm]</b>  | 490      | <b>Power electric [kW]</b> | 3.200              |
| <b>Net Depth [mm]</b>  | 540      | <b>Loading</b>             | 230 V / 1N - 50 Hz |
| <b>Net Height [mm]</b> | 400      |                            |                    |

# Technical data sheet

Technical drawing



## Conveyor toaster 2x holders with regulation

|              |                                  |          |
|--------------|----------------------------------|----------|
| <b>Model</b> | <b>SAP Code</b>                  | 00004519 |
| TN 30 plus   | <b>A group of articles - web</b> | Toasters |

# Technical data sheet



## Product benefits

### Conveyor toaster 2x holders with regulation

|            |                           |          |
|------------|---------------------------|----------|
| Model      | SAP Code                  | 00004519 |
| TN 30 plus | A group of articles - web | Toasters |

1

#### All-stainless design

only stainless steel intended for food contact is used

- absolutely rust-proof and non-magnetic design
- resists even weak acids easier compliance with hygiene standards (HACCP); easy maintenance and cleaning

2

#### Run and warm-up light

optical possibility to check the status of the device

- the operator immediately knows the on/off, heating/ non-heating state of the appliance

3

#### Separate control for individual sections

the possibility of a heating system separately

- greater variability of use

4

#### Catch container for breadcrumbs

breadcrumbs fall outside the furnace

- no crumbs falling off

5

#### Continuous toaster

automatic toast advance

- greater capacity

6

#### Continuous feed adjustment

possibility to change the speed of the sliding belt

- ideally toasted according to the customer's wishes

7

#### Silicon heaters

immediate onset of heat  
intense radiant heat

- the device can be switched off even during the operating day
- toasted food vigorously and without overheating inside
- faster food preparation

# Technical data sheet

## Technical parameters



### Conveyor toaster 2x holders with regulation

|              |                                  |          |
|--------------|----------------------------------|----------|
| <b>Model</b> | <b>SAP Code</b>                  | 00004519 |
| TN 30 plus   | <b>A group of articles - web</b> | Toasters |

**1. SAP Code:**

00004519

**2. Net Width [mm]:**

490

**3. Net Depth [mm]:**

540

**4. Net Height [mm]:**

400

**5. Net Weight [kg]:**

22.00

**6. Gross Width [mm]:**

515

**7. Gross depth [mm]:**

750

**8. Gross Height [mm]:**

440

**9. Gross Weight [kg]:**

23.00

**10. Device type:**

Electric unit

**11. Construction type of device:**

Table top

**12. Material:**

Stainless steel

**13. Power electric [kW]:**

3,200

**14. Loading:**

230 V / 1N - 50 Hz

**15. Heating element material:**

Silicon tube

**16. Protection of controls:**

IPX4

**17. Toasting time:**

60 – 240

**18. Removable rear wall of the device:**

Yes

**19. Indicators:**

operation and warm-up

**20. Width of internal part [mm]:**

305

**21. Depth of internal part [mm]:**

500

**22. Heating location:**

Upper and lower

**23. Cross-section of conductors CU [mm<sup>2</sup>]:**

0,75