

**Product features** 

Combi convection steam oven electric 5x GN 2/3 automatic cleaning direct steam 230 V		
Model	SAP Code	00011343
EPD 0523 EAM	A group of articles - web	Convection machines



- Steam type: Injection
- Number of GN / EN: 5
- GN / EN size in device: GN 2/3
- GN device depth: 65
- Control type: Touchscreen + buttons
- Display size: 5"
- Humidity control: Yes, indirect measuring
- Advanced moisture adjustment: No
- Delta T heat preparation: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011343	Steam type	Injection
Net Width [mm]	600	Number of GN / EN	5
Net Depth [mm]	690	GN / EN size in device	GN 2/3
Net Height [mm]	670	GN device depth	65
Net Weight [kg]	52.00	Control type	Touchscreen + buttons
Power electric [kW]	3.300	Display size	5"
Loading	230 V / 1N - 50 Hz		



### Technical drawing

Combi convection steam oven electric 5x GN 2/3 automatic cleaning direct steam 230 V			
Model	SAP Code	00011343	
EPD 0523 EAM	A group of articles - web	Convection machines	



**Product benefits** 

Combi convection steam oven electric 5x GN 2/3 automatic cleaning direct steam 230 V			
Model	SAP Code	00011343	
EPD 0523 EAM	A group of articles - web	Convection machines	

1

#### **Direct injection**

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets

2

#### **Touch screen display**

simple intuitive control with unique pictograms, all in Czech

the possibility of using preset programs or manual control

- help with cooking even for less skilled cooks
- the possibility of safe cooking even in the absence of the operator
- creating your own recipes

3

#### A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

 allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously

4

#### **Automatic washing**

integrated chamber washing system the possibility of using liquid and tablet detergents option to use vinegar as a rinse aid the system also descales the micro boiler

 the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 100% hygienic quality

5

#### Six-speed reversible fan

ensures perfect distribution of steam without losing its saturation

its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed 6

#### External temperature probe

temperature probe located outside the cooking area, option of choosing one point or vacuum probe

 positioning outside the cooking chamber extends its life; ensuring total food hygiene safety; HACCP record; control of heat treatment in the absence of the cook

7

#### **USB**

downloading service reports upgrade software playing recipes

- quick fault finding
- transfer of original recipes
- keeping software up to date

8

#### **Temperature range 3°C - 3°C**

heating the chamber in the temperature range of 30 to 300  $^{\circ}\text{C}$ 

 Possibility to prepare a large variety of dishes, from low-temperature baking to grilling, gratinating, etc.

9

#### **Stainless steel construction**

construction material is high quality stainless steel ensuring long life high hygiene standard

safe food preparation; long service life; easy cleaning



### Technical parameters

Combi convection steam oven el	ectric 5x GN 2/3 autor	matic cleaning direct steam 230 V			
Model	SAP Code	00011343			
EPD 0523 EAM	A group of articles - web	Convection machines			
<b>1. SAP Code:</b> 00011343		<b>15. Adjustable feet:</b> Yes			
<b>2. Net Width [mm]:</b> 600		<b>16. Humidity control:</b> Yes, indirect measuring			
3. Net Depth [mm]: 690 4. Net Height [mm]: 670		17. Stacking availability: Yes  18. Control type: Touchscreen + buttons			
			<b>5. Net Weight [kg]:</b> 52.00		<b>19. Additional information:</b> possibility of reverse door opening - handle on the right side (must be specified when ordering)
6. Gross Width [mm]: 810  7. Gross depth [mm]: 700  8. Gross Height [mm]: 780  9. Gross Weight [kg]: 130.00		20. Steam type: Injection  21. Sturdier version: No  22. Chimney for moisture extraction: Yes  23. Delayed start: Yes			
			LO. Device type: Electric unit		24. Display size: 5"
			1. Power electric [kW]: 3.300		25. Delta T heat preparation: Yes
			<b>22. Loading:</b> 230 V / 1N - 50 Hz		26. Unified finishing of meals EasyService: Yes
<b>13. Material:</b> AISI 304		27. Night cooking: Yes			
14. Exterior color of the device:		28. Washing system:			

Stainless steel

Open



### Technical parameters

Combi convection steam oven	electric 5v GN 2/2 autor	matic cleaning direct steam 230 V
Model	SAP Code	00011343
EPD 0523 EAM	A group of articles - web	Convection machines
<b>29. Detergent type:</b> Liquid washing detergent + water rinse		<b>43. Interior lighting:</b> Yes
<b>30. Multi level cooking:</b> Drawer program - control of heat treatment for each dish separately		<b>44. Low temperature heat treatment:</b> Yes
31. Advanced moisture adjustment:		45. Number of fans:
<b>B2. Slow cooking:</b> from 50 °C		46. Number of fan speeds:
33. Fan stop: Interruption when door is opened, not braked		<b>47. Number of programs:</b> 1000
<b>34. Lighting type:</b> LED lighting in the door, on one side		<b>48. USB port:</b> Yes, for uploading recipes and updating firmware
<b>35. Cavity material and shape:</b> AISI 304, with rounded corners for easy cleaning		<b>49. Door constitution:</b> Vented safety double glass, removable for easy cleaning
<b>86. Reversible fan:</b> Yes		<b>50. Number of preset programs:</b> 100
7. Sustaince box: Yes		51. Number of recipe steps:
8. Heating element material: Incoloy		<b>52. Minimum device temperature [°C]:</b> 50
9. Probe: Optional		53. Maximum device temperature [°C]: 300
90. Shower: Manual (optional)		<b>54. Device heating type:</b> Combination of steam and hot air
<b>31. Distance between the layers [mm]:</b> 74		55. HACCP: Yes
42. Smoke-dry function:		56. Number of GN / EN:

5

Yes



### Technical parameters

Combi convection steam oven electric 5x GN 2/3 automatic cleaning direct steam 230 V		
Model	SAP Code	00011343
EPD 0523 EAM	A group of articles - web	Convection machines
<b>57. GN / EN size in device:</b> GN 2/3		<b>60. Cross-section of conductors CU [mm²]:</b> 0,75
<b>58. GN device depth:</b> 65		<b>61. Diameter nominal:</b> DN 50
<b>59. Food regeneration:</b> Yes		<b>62. Water supply connection:</b> 3/4"

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com