Technical data sheet

Product features

High-capacity boiling kettle gas indirect 300 l with automatic water charge 230 V / 1N		
Model	**SAP Code**	00019667
BIQ 90/140 300 G AWF	**A group of articles - web**	Boiling kettles



- Device type: Gas unit
- Device heating type: Indirect
- Ignition: Electric
- Steam pressure regulation: Automatic - the pressure switch regulates the performance of the device
- Filling : Mechanical cock
- Jacket filling: Automatic
- Drain valve diameter: 2”
- Basin dimensions [mm x mm x mm]: 1160x540x440/490
- Basin volume [l]: 300
- Usable volume [l]: 280


SAP Code	00019667	**Power gas [kW]**	40.000
Net Width [mm]	1400	**Type of gas**	Natural gas, propane butane
Net Depth [mm]	928	**Basin volume [l]**	300
Net Height [mm]	900	**Usable volume [l]**	280
Net Weight [kg]	250.00	**Basin dimensions [mm x mm x mm]**	1160x540x440/490
Power electric [kW]	0.023	**Device heating type**	Indirect
Loading	230 V / 1N - 50 Hz	**Steam pressure regulation**	Automatic - the pressure switch regulates the performance of the device

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical drawing

High-capacity boiling kettle gas indirect 300 l with automatic water charge 230 V / 1N		
Model	**SAP Code**	00019667
BIQ 90/140 300 G AWF	**A group of articles - web**	Boiling kettles



RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Product benefits

High-capacity boiling kettle gas indirect 300 l with automatic water charge 230 V / 1N		
Model	**SAP Code**	00019667
BIQ 90/140 300 G AWF	**A group of articles - web**	Boiling kettles

1 Top cover in front panel design

thanks to the design, the lines of the front panel and the lid are unified, the designed design allows easy maintenance by the user

- thanks to the design, the condensate is drawn to the back of the lid, eliminating the risk of scalding the operator with hot condensate; the user saves time and energy when maintaining the product

2 Ergonomic extended handle

even people of smaller stature can comfortably lift the lid to the fully open state

- the operator will not be scalded by steam when the lid is raised to the fully open position.

3 Sloped bottom for the sink

the entire volume of the container will flow out without the need to carry the food to the sink

- no residual puddles on the bottom of the cooking vessel; eliminates losses when food is poured out of the cooking vessel

4 Reinforced bottom without deformations

thanks to the reinforcements in the intermediate shell, the service life of the duplicator is extended, there is no deformation due to heat and expansion of the material

- several times longer life of the cooking vessel, where the reinforcements prevent tearing or deformation; the user does not have to replace the product with a new one after years of use, thus saving costs

5 Spill-resistant design controls

ergonomically comfortable, preventing water from entering the device

- due to the sufficient coverage of the controls, water does not leak into the device, thus prolonging the life of the control or eliminating the potential risk of leakage into the functional components of the device

6 Lines in the container

the operator knows at a glance how much food is inside the cooking vessel

- time-saving for the product operator when filling water or measuring the total quantity of food to be prepared

7 Duplicator automatic venting

thanks to the integrated pressure switch, the pressure in the intermediate casing is automatically regulated

- the user can concentrate on food preparation or ingredients as he does not have to monitor the pressure in the intermediate vessel.

8 Automatic duplicator allowance

due to automatic filling/offering, the operator does not have to stand for the device to fill and check the boiler filling

- the user of the appliance can concentrate on the preparation work instead of watching the water level in the intermediate vessel. thanks to automatic draining, the risk of damage to the intermediate pan and heating elements due to missing liquid is eliminated.

9 Rotatable filling arm

convenient filling of the duplicator container, the hanger is used for maintenance and cleaning of the cooking container

- convenient filling and cleaning of the cooking vessel, but the hanger does not interfere with the cooking vessel, thanks to its position on the top plate

10 Integrated waste overflow

condensed water drains directly from the top plate

- elimination of the risk of the operator slipping on the wet floor; excess liquids are drained directly into the central waste and not in front of or under the equipment

11 Molded top plate

easier operation and cleanability, water does not flow over the edge on controls and service
the top plate retains its stiffness without deformation over time due to use

- operator safety when using the product, hygiene and strength of the equipment

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

High-capacity boiling kettle gas indirect 300 l with automatic water charge 230 V / 1N		
Model	**SAP Code**	00019667
BIQ 90/140 300 G AWF	**A group of articles - web**	Boiling kettles

1. **SAP Code:**
   00019667
2. **Net Width [mm]:**
   1400
3. **Net Depth [mm]:**
   928
4. **Net Height [mm]:**
   900
5. **Net Weight [kg]:**
   250.00
6. **Gross Width [mm]:**
   1435
7. **Gross depth [mm]:**
   1030
8. **Gross Height [mm]:**
   1085
9. **Gross Weight [kg]:**
   260.00
10. **Device type:**
    Gas unit
11. **Construction type of device:**
    Stationary
12. **Power electric [kW]:**
    0.023
13. **Loading:**
    230 V / 1N - 50 Hz
14. **Power gas [kW]:**
    40.000
15. **Ignition:**
    Electric
16. **Type of gas:**
    Natural gas, propane butane
17. **Protection of controls:**
    IPX4
18. **Exterior color of the device:**
    Stainless steel
19. **Material:**
    AISI 304 top plate and cladding
20. **Indicators:**
    operation and warm-up
21. **Drain valve diameter:**
    2"
22. **Worktop type:**
    Molded - comfortable cleaning maintenance
23. **Worktop material:**
    AISI 304
24. **Worktop Thickness [mm]:**
    2.00
25. **Surface finish:**
    polished stainless steel
26. **Device heating type:**
    Indirect
27. **Basin volume [l]:**
    300
28. **Basin dimensions [mm x mm x mm]:**
    1160x540x440/490

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

High-capacity boiling kettle gas indirect 300 l with automatic water charge 230 V / 1N		
Model	**SAP Code**	00019667
BIQ 90/140 300 G AWF	**A group of articles - web**	Boiling kettles

29. Volume capacity of the container [l]:
300.00

30. Maximum device temperature [°C]:
100

31. Minimum device temperature [°C]:
30

32. Number of power control stages:
2

33. Safety element:
manometer, safety valve

34. Safety thermocouple:
Yes

35. Safety thermostat:
Yes

36. Safety thermostat up to x ° C:
150

37. Adjustable feet:
Yes

38. Bottom thickness:
2.50

39. Bottom material:
AISI 316

40. Type of pan:
Fixed

41. Usable volume [l]:
280

42. Filling :
Mechanical cock

43. Jacket filling:
Automatic

44. Basin shape:
Practically shaped bathtub spout to minimize spillage

45. Steam pressure regulation:
Automatic - the pressure switch regulates the performance of the device

46. Type of drain valve:
conical

47. Overflow:
Yes

48. Manometer:
Yes

49. Water filling type:
Cold

50. Connection to a ball valve:
1/2

51. Water supply connection:
1/2”

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062