

Technical data sheet

Product features



Fry-top griddle plate 31x65 electric chromed grooved on open cabinet

Model	SAP Code	00012400
FTRC 90/40 E	A group of articles - web	Grills and grill plates



- Top type: Grooved
- Worktop material: Chrome plated steel
- Maximum device temperature [°C]: 300

SAP Code	00012400	Net Weight [kg]	71.00
Net Width [mm]	400	Power electric [kW]	6.000
Net Depth [mm]	900	Loading	400 V / 3N - 50 Hz
Net Height [mm]	900	Top type	Grooved

Technical data sheet



Product benefits

Fry-top griddle plate 31x65 electric chromed grooved on open cabinet

Model	SAP Code	00012400
FTRC 90/40 E	A group of articles - web	Grills and grill plates

1

All-stainless design

long life
corrosion resistance of the top plate material

2

Degree of protection of the control elements IPX4

maintenance-free system
resistance to splash water
long life

3

Outlet for waste liquids

ensures that oil drips into the socket

4

High detachable hem

better hygienic conditions
preventing grease from splashing onto
ancillary equipment

5

Grooved plate made of chrome-plated steel

the product bakes less and is easier to clean
a good warming of the meat with a groove

Technical data sheet

Technical parameters



Fry-top griddle plate 31x65 electric chromed grooved on open cabinet

Model	SAP Code	00012400
FTRC 90/40 E	A group of articles - web	Grills and grill plates

1. SAP Code:

00012400

2. Net Width [mm]:

400

3. Net Depth [mm]:

900

4. Net Height [mm]:

900

5. Net Weight [kg]:

71.00

6. Gross Width [mm]:

970

7. Gross depth [mm]:

440

8. Gross Height [mm]:

1140

9. Gross Weight [kg]:

80.00

10. Device type:

Electric unit

11. Construction type of device:

Stationary

12. Power electric [kW]:

6.000

13. Loading:

400 V / 3N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 304 top plate, AISI 430 cladding

16. Worktop material:

Chrome plated steel

17. Maximum device temperature [°C]:

300

18. Minimum device temperature [°C]:

50

19. Adjustable feet:

Yes

20. Top type:

Grooved

21. Cross-section of conductors CU [mm²]:

1