

Technical data sheet



Product features

Fry-top griddle plate 32x48 gas grooved without cabinet

Model	SAP Code	00001160
FTR 30 GL	A group of articles - web	Grills and grill plates



- Top type: Grooved
- Griddle dimensions [mm x mm]: 320 x 480
- Griddle thickness [mm]: 10.00
- Container for liquid fat: Yes
- Maximum device temperature [°C]: 300
- Surface finish: sandblasted surface without coating
- Removable rim: No
- Ignition: Piezo

SAP Code	00001160	Power gas [kW]	4.000
Net Width [mm]	328	Type of gas	Natural gas, propane butane
Net Depth [mm]	609	Griddle dimensions [mm x mm]	320 x 480
Net Height [mm]	290	Top type	Grooved
Net Weight [kg]	23.00		

Technical data sheet



Product benefits

Fry-top griddle plate 32x48 gas grooved without cabinet

Model	SAP Code	00001160
FTR 30 GL	A group of articles - web	Grills and grill plates

1

Safety element – thermocouple

safe service for staff
there is no unnecessary gas leakage
long life

2

All-stainless design

long life
resistance of AISI 304 stainless steel material
the material does not cut

3

Degree of protection of the control elements IPX4

maintenance-free system
resistance to splash water
long life

4

Outlet for waste liquids

ensures that oil drips into the socket

5

High non-removable hem

better hygienic conditions
preventing grease from splashing onto
ancillary equipment

6

Ribbed steel plate

fast heat transfer and the surface will not be scratched
a good warming of the meat with a groove

7

Cooking unit for use on a table or on a base

variable use
the possibility of placement in smaller spaces

Technical data sheet



Technical parameters

Fry-top griddle plate 32x48 gas grooved without cabinet

Model	SAP Code	00001160
FTR 30 GL	A group of articles - web	Grills and grill plates

1. SAP Code:

00001160

2. Net Width [mm]:

328

3. Net Depth [mm]:

609

4. Net Height [mm]:

290

5. Net Weight [kg]:

23.00

6. Gross Width [mm]:

395

7. Gross depth [mm]:

705

8. Gross Height [mm]:

482

9. Gross Weight [kg]:

29.00

10. Device type:

Gas unit

11. Construction type of device:

Table top

12. Power gas [kW]:

4.000

13. Ignition:

Piezo

14. Type of gas:

Natural gas, propane butane

15. Protection of controls:

IPX4

16. Material:

AISI 430

17. Surface finish:

sandblasted surface without coating

18. Maximum device temperature [°C]:

300

19. Minimum device temperature [°C]:

50

20. Adjustable feet:

Yes

21. Griddle dimensions [mm x mm]:

320 x 480

22. Griddle thickness [mm]:

10.00

23. Container for liquid fat:

Yes

24. Removable rim:

No

25. Uniform heating:

Yes

26. Top type:

Grooved

27. Connection to a ball valve:

1/2