

# Technical data sheet



## Product features

### Cooking range gas 2x burner on open cabinet

|              |                                  |          |
|--------------|----------------------------------|----------|
| <b>Model</b> | <b>SAP Code</b>                  | 00012303 |
| SP 90/40 G   | <b>A group of articles - web</b> | Stoves   |



- Device type: Gas unit
- Power consumption of the zone 1 [kW]: 8
- Power consumption of the zone 2 [kW]: 5
- Protection of controls: IPX4
- Material: AISI 304 top plate, AISI 430 cladding

|                        |          |                                             |                             |
|------------------------|----------|---------------------------------------------|-----------------------------|
| <b>SAP Code</b>        | 00012303 | <b>Power gas [kW]</b>                       | 16.000                      |
| <b>Net Width [mm]</b>  | 400      | <b>Type of gas</b>                          | Natural gas, propane butane |
| <b>Net Depth [mm]</b>  | 900      | <b>Number of zones</b>                      | 2                           |
| <b>Net Height [mm]</b> | 900      | <b>Power consumption of the zone 1 [kW]</b> | 8                           |
| <b>Net Weight [kg]</b> | 44.00    | <b>Power consumption of the zone 2 [kW]</b> | 5                           |

# Technical data sheet



## Product benefits

### Cooking range gas 2x burner on open cabinet

|              |                                  |          |
|--------------|----------------------------------|----------|
| <b>Model</b> | <b>SAP Code</b>                  | 00012303 |
| SP 90/40 G   | <b>A group of articles - web</b> | Stoves   |

1

#### Massive construction of burners

high performance and efficiency  
brass burners removable  
eternal flame  
long life  
demountable

2

#### Hygienic moldings of the top plate

absence of sharp corners and edges (potential places where dirt could stick)  
smooth transitions

3

#### Degree of protection of the control elements IPX4

maintenance-free system  
resistance to splash water  
long life

4

#### All-stainless design

long life  
resistance of a ground steel plate with a thickness of 10 mm

5

#### Safety element – thermocouple

safe operation for personnel  
there is no overheating and damage to the thallus  
long life

6

#### Variability

the possibility of adding to the current line  
easy possibility of creating one module  
long life

# Technical data sheet

## Technical parameters



### Cooking range gas 2x burner on open cabinet

|              |                                  |          |
|--------------|----------------------------------|----------|
| <b>Model</b> | <b>SAP Code</b>                  | 00012303 |
| SP 90/40 G   | <b>A group of articles - web</b> | Stoves   |

**1. SAP Code:**

00012303

**2. Net Width [mm]:**

400

**3. Net Depth [mm]:**

900

**4. Net Height [mm]:**

900

**5. Net Weight [kg]:**

44.00

**6. Gross Width [mm]:**

970

**7. Gross depth [mm]:**

440

**8. Gross Height [mm]:**

1140

**9. Gross Weight [kg]:**

56.00

**10. Device type:**

Gas unit

**11. Construction type of device:**

With substructure

**12. Power gas [kW]:**

16.000

**13. Type of gas:**

Natural gas, propane butane

**14. Protection of controls:**

IPX4

**15. Material:**

AISI 304 top plate, AISI 430 cladding

**16. Worktop material:**

AISI 304

**17. Worktop Thickness [mm]:**

1.50

**18. Number of zones:**

2

**19. Power consumption of the zone 1 [kW]:**

8

**20. Power consumption of the zone 2 [kW]:**

5

**21. Grid material:**

Stainless steel

**22. Service accessibility:**

Trough the frontal panel

**23. Safety thermocouple:**

Yes

**24. Adjustable feet:**

Yes

**25. Number of burners/hot plates:**

2

**26. Type of gas cooking zones:**

Classic

**27. Burner type:**

Brass, detachable

**28. Connection to a ball valve:**

1/2