

Technical data sheet

Product features



Fry-top griddle plate 31x65 electric smooth on open cabinet 400 V

Model	SAP Code	00012295
FTH 90/40 E	A group of articles - web	Grills and grill plates



- Top type: Smooth
- Griddle thickness [mm]: 15.00
- Worktop material: Sandblasted steel
- Maximum device temperature [°C]: 300

SAP Code	00012295	Net Weight [kg]	71.00
Net Width [mm]	400	Power electric [kW]	6.000
Net Depth [mm]	900	Loading	400 V / 3N - 50 Hz
Net Height [mm]	900	Top type	Smooth


Technical data sheet

Technical drawing



Fry-top griddle plate 31x65 electric smooth on open cabinet 400 V

Model	SAP Code	00012295
FTH 90/40 E	A group of articles - web	Grills and grill plates



Technical data sheet



Product benefits

Fry-top griddle plate 31x65 electric smooth on open cabinet 400 V

Model	SAP Code	00012295
FTH 90/40 E	A group of articles - web	Grills and grill plates

1

All-stainless design

- long life
- corrosion resistance of the top plate material
 - savings on service interventions
 - easier and faster operation

2

Degree of protection of the control elements IPX4

- maintenance-free system
- resistance to splash water
- long life
 - savings on service interventions
 - easy cleaning and maintenance of equipment

3

Outlet for waste liquids

- ensures that oil drips into the socket
 - easy maintenance
 - easy cleaning

4

High detachable hem

- better hygienic conditions
- preventing grease from splashing onto ancillary equipment
 - easy maintenance
 - easy cleaning

5

Smooth steel plate

- good heat transfer and the surface does not get scratched
- enables preparation on smooth or grooved plates
 - time-saving for food preparation
 - no reheating and long cooking times

Technical data sheet

Technical parameters



Fry-top griddle plate 31x65 electric smooth on open cabinet 400 V

Model	SAP Code	00012295
FTH 90/40 E	A group of articles - web	Grills and grill plates

1. SAP Code:

00012295

2. Net Width [mm]:

400

3. Net Depth [mm]:

900

4. Net Height [mm]:

900

5. Net Weight [kg]:

71.00

6. Gross Width [mm]:

970

7. Gross depth [mm]:

440

8. Gross Height [mm]:

1140

9. Gross Weight [kg]:

80.00

10. Device type:

Electric unit

11. Construction type of device:

Stationary

12. Power electric [kW]:

6.000

13. Loading:

400 V / 3N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 304 top plate, AISI 430 cladding

16. Worktop material:

Sandblasted steel

17. Worktop Thickness [mm]:

15.00

18. Maximum device temperature [°C]:

300

19. Minimum device temperature [°C]:

50

20. Adjustable feet:

Yes

21. Griddle thickness [mm]:

15.00

22. Top type:

Smooth

23. Cross-section of conductors CU [mm²]:

1