

Technical data sheet

Product features



High-capacity boiling kettle electric indirect 200 l

Model	SAP Code	00019665
BIQ 90/100 200 E	A group of articles - web	Boiling kettles



- Device type: Electric unit
- Device heating type: Indirect
- Steam pressure regulation: Automatic - the pressure switch regulates the performance of the device
- Filling : Mechanical cock
- Jacket filling: Semi-automatic
- Drain valve diameter: 2"
- Basin dimensions [mm x mm x mm]: 760x540x440/490
- Basin volume [l]: 200
- Usable volume [l]: 183

SAP Code	00019665	Loading	400 V / 3N - 50 Hz
Net Width [mm]	1000	Basin volume [l]	200
Net Depth [mm]	928	Usable volume [l]	183
Net Height [mm]	900	Basin dimensions [mm x mm x mm]	760x540x440/490
Net Weight [kg]	188.00	Device heating type	Indirect
Power electric [kW]	24.000	Steam pressure regulation	Automatic - the pressure switch regulates the performance of the device



Technical data sheet

Technical drawing




High-capacity boiling kettle electric indirect 200 l

Model	SAP Code	00019665
BIQ 90/100 200 E	A group of articles - web	Boiling kettles



E - přívod napětí 400V
WD - přívod vody do duplikátu
W - přívod vody



Technical data sheet



Product benefits

High-capacity boiling kettle electric indirect 200 l

Model	SAP Code	00019665
BIQ 90/100 200 E	A group of articles - web	Boiling kettles

1

Top cover in front panel design

thanks to the design, the lines of the front panel and the lid are unified, the designed design allows easy maintenance by the user

- thanks to the design, the condensate is drawn to the back of the lid, eliminating the risk of scalding the operator with hot condensate; the user saves time and energy when maintaining the product

2

Ergonomic extended handle

even people of smaller stature can comfortably lift the lid to the fully open state

- the operator will not be scalded by steam when the lid is raised to the fully open position.

3

Sloped bottom for the sink

the entire volume of the container will flow out without the need to carry the food to the sink

- no residual puddles on the bottom of the cooking vessel; eliminates losses when food is poured out of the cooking vessel

4

Reinforced bottom without deformations

thanks to the reinforcements in the intermediate shell, the service life of the duplicator is extended, there is no deformation due to heat and expansion of the material

- several times longer life of the cooking vessel, where the reinforcements prevent tearing or deformation; the user does not have to replace the product with a new one after years of use, thus saving costs

5

Spill-resistant design controls

ergonomically comfortable, preventing water from entering the device

- due to the sufficient coverage of the controls, water does not leak into the device, thus prolonging the life of the control or eliminating the potential risk of leakage into the functional components of the device

6

Lines in the container

the operator knows at a glance how much food is inside the cooking vessel

- time-saving for the product operator when filling water or measuring the total quantity of food to be prepared

7

Duplicator automatic venting

thanks to the integrated pressure switch, the pressure in the intermediate casing is automatically regulated

- the user can concentrate on food preparation or ingredients as he does not have to monitor the pressure in the intermediate vessel.

8

Rotatable filling arm

convenient filling of the duplicator container, the hanger is used for maintenance and cleaning of the cooking container

- convenient filling and cleaning of the cooking vessel, but the hanger does not interfere with the cooking vessel, thanks to its position on the top plate

9

Integrated waste overflow

condensed water drains directly from the top plate

- elimination of the risk of the operator slipping on the wet floor; excess liquids are drained directly into the central waste and not in front of or under the equipment

10

Molded top plate

easier operation and cleanability, water does not flow over the edge on controls and service the top plate retains its stiffness without deformation over time due to use

- operator safety when using the product, hygiene and strength of the equipment

11

Integrated waste overflow

the operator can check the pressure in the intermediate casing

- the operator receives real-time information about the pressure in the intermediate layer and thus checks the correctness of the function and the efficiency of the energy used

12

A pre-prescribed upper lid with a lifting mechanism

lid holds open in different positions

- when partially opened, there is no large heat loss and thus energy savings are achieved

Technical data sheet

Technical parameters



High-capacity boiling kettle electric indirect 200 l

Model	SAP Code	00019665
BIQ 90/100 200 E	A group of articles - web	Boiling kettles

1. SAP Code:

00019665

2. Net Width [mm]:

1000

3. Net Depth [mm]:

928

4. Net Height [mm]:

900

5. Net Weight [kg]:

188.00

6. Gross Width [mm]:

1035

7. Gross depth [mm]:

1030

8. Gross Height [mm]:

1085

9. Gross Weight [kg]:

196.00

10. Device type:

Electric unit

11. Construction type of device:

Stationary

12. Power electric [kW]:

24.000

13. Loading:

400 V / 3N - 50 Hz

14. Protection of controls:

IPX4

15. Exterior color of the device:

Stainless steel

16. Material:

AISI 304 top plate and cladding

17. Indicators:

operation and warm-up

18. Drain valve diameter:

2"

19. Worktop type:

Molded - comfortable cleaning maintenance

20. Worktop material:

AISI 304

21. Worktop Thickness [mm]:

2.00

22. Surface finish:

polished stainless steel

23. Device heating type:

Indirect

24. Basin volume [l]:

200

25. Basin dimensions [mm x mm x mm]:

760x540x440/490

26. Volume capacity of the container [l]:

200.00

27. Maximum device temperature [°C]:

100

28. Minimum device temperature [°C]:

30

Technical data sheet



Technical parameters

High-capacity boiling kettle electric indirect 200 l

Model	SAP Code	00019665
BIQ 90/100 200 E	A group of articles - web	Boiling kettles

29. Service accessibility:

Trough the frontal panel

30. Safety element:

manometer
long handle

31. Safety thermostat:

Yes

32. Safety thermostat up to x ° C:

150

33. Adjustable feet:

Yes

34. Bottom thickness:

2.50

35. Bottom material:

AISI 316

36. Type of pan:

Fixed

37. Usable volume [l]:

183

38. Filling :

Mechanical cock

39. Jacket filling:

Semi-automatic

40. Basin shape:

Practically shaped bathtub spout to minimize spillage

41. Steam pressure regulation:

Automatic - the pressure switch regulates the performance of the device

42. Type of drain valve:

conical

43. Overflow:

Yes

44. Manometer:

Yes

45. Water filling type:

Cold

46. Cross-section of conductors CU [mm²]:

10

47. Water supply connection:

1/2"