

Technical data sheet



Product features

Freezer cabinet 340 l glass door 7x grid, white

| | | |
|--------------|----------------------------------|------------------------------------|
| Model | SAP Code | 00009369 |
| HF 400/G | A group of articles - web | Refrigeration and freezer cabinets |



- Chamber volume [l]: 340
- Minimum device temperature [°C]: -18
- Maximum device temperature [°C]: -22
- Control type: Digital
- Door lock: Yes
- Opening of device: Hinges on the right

| | | | |
|----------------------------|--------------------|----------------------------------------|-------|
| SAP Code | 00009369 | Chamber volume [l] | 340 |
| Net Width [mm] | 585 | Gross Volume [m3] | 0.784 |
| Net Depth [mm] | 600 | Net Volume [m3] | 0.651 |
| Net Height [mm] | 1855 | Minimum device temperature [°C] | -18 |
| Net Weight [kg] | 69.00 | Maximum device temperature [°C] | -22 |
| Power electric [kW] | 0.210 | Refrigerant | R600a |
| Loading | 230 V / 1N - 50 Hz | | |

Technical data sheet



Technical drawing

Freezer cabinet 340 l glass door 7x grid, white

| | | |
|--------------|----------------------------------|------------------------------------|
| Model | SAP Code | 00009369 |
| HF 400/G | A group of articles - web | Refrigeration and freezer cabinets |

Technical data sheet



Product benefits

Freezer cabinet 340 l glass door 7x grid, white

| | | |
|--------------|----------------------------------|------------------------------------|
| Model | SAP Code | 00009369 |
| HF 400/G | A group of articles - web | Refrigeration and freezer cabinets |

1

Quality insulation

minimal heat loss

- saving electricity
- less wear and tear on the compressor due to less frequent switching

2

Two-sided opening

possibility to change the opening from the right to the left side

- greater variability of use

3

All-stainless design

outer shell

only stainless steel intended for food contact is used

good maintenance

zero contamination

resists even weaker acids

- long service life and high durability

4

Automatic defrosting

maintenance-free operation

continuous defrosting

- zero requirement for frost control by the operator

5

Wheels, legs

maintenance-free operation

continuous defrosting

- easy handling even when cleaning

6

Glass door

visible content

- saving on electricity, as the operator does not have to open the door so many times to check the contents of the fridge

Technical data sheet



Technical parameters

Freezer cabinet 340 l glass door 7x grid, white

| | | |
|--------------|----------------------------------|------------------------------------|
| Model | SAP Code | 00009369 |
| HF 400/G | A group of articles - web | Refrigeration and freezer cabinets |

1. SAP Code:

00009369

2. Net Width [mm]:

585

3. Net Depth [mm]:

600

4. Net Height [mm]:

1855

5. Net Weight [kg]:

69.00

6. Gross Width [mm]:

600

7. Gross depth [mm]:

650

8. Gross Height [mm]:

2010

9. Gross Weight [kg]:

84.00

10. Device type:

Electric unit

11. Power electric [kW]:

0.210

12. Loading:

230 V / 1N - 50 Hz

13. Refrigerant:

R600a

14. Cooling type:

Static with fan

15. Material:

Stainless steel

16. Min ambient temperature [°C]:

10

17. Max ambient temperature [°C]:

43

18. Device properties 2:

Freezing

19. Chamber volume [l]:

340

20. Gross Volume [m3]:

0.784

21. Net Volume [m3]:

0.651

22. Adjustable feet:

Yes

23. Opening of device:

Hinges on the right

24. Gasket:

Yes

25. Number of doors:

1

26. Unit:

Yes

27. Control type:

Digital

28. Door lock:

Yes

Technical data sheet



Technical parameters

Freezer cabinet 340 l glass door 7x grid, white

| | | |
|--------------|----------------------------------|------------------------------------|
| Model | SAP Code | 00009369 |
| HF 400/G | A group of articles - web | Refrigeration and freezer cabinets |

29. Minimum device temperature [°C]:

-18

31. Number of grids:

7

30. Maximum device temperature [°C]:

-22

32. Cross-section of conductors CU [mm²]:

0,5