

Product features

Combi convection steam oven electric 10x GN 1/1 direct steam 400 V		
Model	SAP Code	00011355
EPD 1011 E	A group of articles - web	Convection machines
		Steam type: Injection

- Steam type: InjectionNumber of GN / EN: 10GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Touchscreen + buttons
- Display size: 5"
- Humidity control: Yes, indirect measuring
- Advanced moisture adjustment: No
- Delta T heat preparation: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011355	Steam type	Injection
Net Width [mm]	870	Number of GN / EN	10
Net Depth [mm]	750	GN / EN size in device	GN 1/1
Net Height [mm]	1050	GN device depth	65
Net Weight [kg]	100.00	Control type	Touchscreen + buttons
Power electric [kW]	12.600	Display size	5"
Loading	400 V / 3N - 50 Hz		



Technical drawing

Combi convection steam oven electric 10x GN 1/1 direct steam 400 V			
Model	SAP Code	00011355	
EPD 1011 E	A group of articles - web	Convection machines	



Product benefits

Combi convection steam oven electric 10x GN 1/1 direct steam 400 V			
Model	SAP Code	00011355	
EPD 1011 E	A group of articles - web	Convection machines	

1

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets

2

Touch screen display

simple intuitive control with unique pictograms, all in Czech

the possibility of using preset programs or manual control

- help with cooking even for less skilled cooks
- the possibility of safe cooking even in the absence of the operator
- creating your own recipes

3

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

 allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously

4

Automatic washing

integrated chamber washing system the possibility of using liquid and tablet detergents option to use vinegar as a rinse aid the system also descales the micro boiler

 the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 100% hygienic quality

5

Six-speed reversible fan

ensures perfect distribution of steam without losing its saturation

its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed 6

External temperature probe

temperature probe located outside the cooking area, option of choosing one point or vacuum probe

 positioning outside the cooking chamber extends its life; ensuring total food hygiene safety; HACCP record; control of heat treatment in the absence of the cook

7

USB

downloading service reports upgrade software playing recipes

- quick fault finding
- transfer of original recipes
- keeping software up to date

8

Temperature range 3°C - 3°C

heating the chamber in the temperature range of 30 to 300 $^{\circ}\text{C}$

 Possibility to prepare a large variety of dishes, from low-temperature baking to grilling, gratinating, etc.

9

Stainless steel construction

construction material is high quality stainless steel ensuring long life high hygiene standard

safe food preparation; long service life; easy cleaning



Technical parameters

Combi convection steam oven elec	ctric 10x GN 1/1 dire	ect steam 400 V
Model	SAP Code	00011355
EPD 1011 E	A group of articles - web	Convection machines
1. SAP Code: 00011355		14. Exterior color of the device: Stainless steel
2. Net Width [mm]: 870		15. Adjustable feet: Yes
3. Net Depth [mm]: 750		16. Humidity control: Yes, indirect measuring
4. Net Height [mm]: 1050		17. Stacking availability: Yes
5. Net Weight [kg]: 100.00		18. Control type: Touchscreen + buttons
6. Gross Width [mm]: 940		19. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)
7. Gross depth [mm]: 900		20. Steam type: Injection
8. Gross Height [mm]: 1160		21. Sturdier version: No
9. Gross Weight [kg]: 130.00		22. Chimney for moisture extraction: Yes
10. Device type: Electric unit		23. Delayed start: Yes
11. Power electric [kW]: 12.600		24. Display size: 5"
12. Loading: 400 V / 3N - 50 Hz		25. Delta T heat preparation: Yes
13. Material: AISI 304		26. Unified finishing of meals EasyService: Yes
27. Night cooking: Yes		42. Low temperature heat treatment: Yes



Technical parameters

Combi convection steam ov	en electric 10x GN 1/1 dire	ct steam 400 V
Model	SAP Code	00011355
EPD 1011 E	A group of articles - web	Convection machines
28. Multi level cooking: Drawer program - control of dish separately	heat treatment for each	43. Number of fans:
29. Advanced moisture adjust	ment:	44. Number of fan speeds:
30. Slow cooking: from 50 °C		45. Number of programs: 1000
31. Fan stop: Interruption when door is op	ened, not braked	46. USB port: Yes, for uploading recipes and updating firmware
32. Lighting type: LED lighting in the door, on o	one side	47. Door constitution: Vented safety double glass, removable for easy cleaning
33. Cavity material and shape AISI 304, with rounded corne		48. Number of preset programs:
34. Reversible fan: Yes		49. Number of recipe steps: 9
35. Sustaince box: Yes		50. Minimum device temperature [°C]: 50
36. Heating element material Incoloy	:	51. Maximum device temperature [°C]: 300
37. Probe: Optional		52. Device heating type: Combination of steam and hot air
38. Shower: Manual (optional)		53. HACCP: Yes
39. Distance between the laye	ers [mm]:	54. Number of GN / EN:
40. Smoke-dry function: Yes		55. GN / EN size in device: GN 1/1
41. Interior lighting:		56. GN device depth:

Yes

65



Technical parameters

Combi convection steam oven electric 10x GN 1/1 direct steam 400 V			
Model	SAP Code	00011355	
EPD 1011 E	A group of articles - web	Convection machines	
57. Food regeneration: Yes 58. Cross-section of conductors CU	[mm²]:	59. Diameter nominal: DN 50 60. Water supply connection: 3/4"	